



2021 List of Asphalt Eligible Tyres



Page 2



Page 17



Page 29



Page 40



Page 45



Page 56



Page 63



Page 71



Page 74



Page 83



Page 88



Page 81



Page 94

18"-20/65-18




Domaine : Rallye Asphalte

Dimension : 20 / 65 – 18

Plan de la sculpture : Pilot Sport R

Entaillement Surfamique dans fenêtre réglementaire : 21,51 %

Clermont-Ferrand le 05/12/2013



17"-19/63-17




Domaine : Rallye Asphalte

Dimension : 19 / 63 – 17

Plan de la sculpture : Pilot Sport R

Entaillement surfacique sur fenêtre réglementaire : 21,51 %

Clermont-Ferrand le 05/12/2013



16"-19/60-16




Domaine : Rallye Asphalte

Dimension : 19 / 60 – 16

Plan de la sculpture : Pilot Sport R

Entaillement surfacique sur fenêtre réglementaire : 21,51 %

Clermont-Ferrand le 05/12/2013



15"-19/58-15




Domaine : Rallye Asphalte

Dimension : 19 / 58 – 15

Plan de la sculpture : Pilot Sport R

Entaillement surfacique sur fenêtre réglementaire : 21,51 %

Clermont-Ferrand le 05/12/2013



18"-20/65-18

Domaine : Rallye Asphalte Wet

Dimension : 20 / 65 - 18


Plan de la sculpture : Pilot Sport A MW1

Entaillement Surfacique dans fenetre

règlementaire > ou = 27.5 % avec les entailles > 1.8 mm de profondeur comme avec les entailles > 5.5 mm de profondeur.



Clermont-Ferrand le 03/07/2019



MANUFACTURE FRANCAISE DES PNEUMATIQUES
MICHELIN CLERMONT-FERRAND
PROPRIETE EXCLUSIVE DE NOTRE SOCIETE
REPRODUCTION OU UTILISATION INTERDITE SANS
NOTRE ACCORD ECRIT

17"-19/63-17

Domaine : Rallye Asphalte Wet

Dimension : 19 / 63 - 17

Plan de la sculpture : Pilot Sport A MW1

Entaillement surfacique dans fenêtre


règlementaire > ou = 27.5 % avec les entailles > 1.8 mm de profondeur comme avec les entailles > 5.5 mm de profondeur.



Clermont-Ferrand le 18/09/2019

Côté Extérieur véhicule

Côté Intérieur véhicule



Coupe F-F
Echelle : 1:1

Vue de face
Echelle : 1:1

Coupe B-B
Echelle : 1:1

Coupe C-C
Echelle : 1:1

Coupe D-D
Echelle : 1:1

MANUFACTURE FRANCAISE DES PNEUMATIQUES
MICHELIN CLERMONT-FERRAND
PROPRIETE EXCLUSIVE DE NOTRE SOCIETE
REPRODUCTION OU UTILISATION INTERDITE SANS
NOTRE ACCORD ECRIT

16"-19/60-16

Domaine : Rallye Asphalte Wet

Dimension : 19 / 60 - 16

Plan de la sculpture : Pilot Sport A MW1


Entaillement surfacique dans fenêtre réglementaire > ou = 27.5 % avec les entailles > 1.8 mm de profondeur comme avec les entailles > 5.5 mm de profondeur.



Clermont-Ferrand le 23/09/2019

Côté Extérieur véhicule

Côté Intérieur véhicule




MANUFACTURE FRANCAISE DES PNEUMATIQUES
MICHELIN CLERMONT-FERRAND
PROPRIETE EXCLUSIVE DE NOTRE SOCIETE
REPRODUCTION OU UTILISATION INTERDITE SANS
NOTRE ACCORD ECRIT

18" – 20/65-18

Domaine : Rallye Asphalte
 Dimension : 20 / 65 – 18
 Plan de la sculpture : Pilot Sport A
 Entaillement Surfaccique dans fenetre
 réglementaire : 21.74 %



Clermont-Ferrand le 06/08/2020



MANUFACTURE FRANCAISE DES PNEUMATIQUES
 MICHELIN CLERMONT-FERRAND
 PROPRIETE EXCLUSIVE DE NOTRE SOCIETE
 REPRODUCTION OU UTILISATION INTERDITE SANS
 NOTRE ACCORD ECRIT

18"-18/65-18



Clermont-Ferrand le : 15/12/2016
 Domaine : Rallye Asphalte WRC Wet



Dimension : 18 / 65 – 18

Plan de la sculpture : Pilot Sport FW3

Entaillement Surfacique sur entaille $\geq 5,5\text{mm}$ de profondeur : 27.5%

MANUFACTURE FRANÇAISE DES PNEUMATIQUES
 MICHELIN CLERMONT-FERRAND

PROPRIÉTÉ EXCLUSIVE DE NOTRE SOCIÉTÉ.
 RÉPRODUCTION OU UTILISATION INTERDITE SANS
 NOTRE ACCORD ÉCRIT



RGT Only – 24/65-18




Domaine : Rallye Asphalte

Dimension : 24 / 65 - 18

Entaillement surfacique sur une fenêtre de 190 mm de large : 32,8 %

Clermont-Ferrand le 18/12/2013




RGT Only – 24/65-18



Domaine : Rallye Asphalte
Dimension : 24 / 65 - 18
Entaillement surfacique global : 32,8 %

Clermont-Ferrand le 18/12/2013

Pneu Avant Gauche



RGT Only – 29/65-18




Domaine : Rallye Asphalte

Dimension : 29 / 65 - 18

Entaillement surfacique sur fenêtre de 249 mm de large : 31 %

Clermont-Ferrand le 18/12/2013



RGT Only – 29/65-18




Domaine : Rallye Asphalte

Dimension : 29 / 65 – 18

Entaillement surfacique sur fenêtre de 249 mm de large : 31 %

Clermont-Ferrand le 18/12/2013



RGT Only – 24/65-18





Domaine : Rallye Asphalte

Dimension : 24/65 R18


Plan de la sculpture : Pilot Sport R

Entaillement Surfaccique dans fenetre réglementaire : 21.7 % à 1.8 mm d'usure
: 17 % à 5.5 mm d'usure


Clermont-Ferrand le 28/02/2018




Coupe E-E



Coupe D-D




Coupe B-B



Coupe F-F

MANUFACTURE FRANCAISE DES PNEUMATIQUES
MICHELIN CLERMONT-FERRAND
PROPRIETE EXCLUSIVE DE NOTRE SOCIETE
REPRODUCTION OU UTILISATION INTERDITE
SANS NOTRE ACCORD ECRIT




Coupe C-C

RGT Only-29/65-18



Domaine : Rallye Asphalte
 Dimension : 29/65 R18
 Plan de la sculpture : Pilot Sport R
 Entaillement Surfacing dans fenêtre réglementaire : 22.6 % à 1.8 mm d'usure
 : 19.2 % à 5.5 mm d'usure


Clermont-Ferrand le 28/02/2018



MANUFACTURE FRANCAISE DES PNEUMATIQUES MICHELIN
 CLERMONT-FERRAND
 PROPRIETE EXCLUSIVE DE NOTRE SOCIETE
 REPRODUCTION OU UTILISATION INTERDITE SANS
 NOTRE ACCORD ECRIT


18"-225/40-18

DMACK Tyres




17"-195/50-17

DMACK Tyres




16"-195/50-16

DMACK Tyres




15"-195/50-15




14"-175/60-14

DMACK Tyres




注: TM字高3mm,线粗1mm,线高0.8mm,圆周六等分




GROOVES SURFACE AREA=4292.808;
CONTROL SURFACE 17360;
 $4292.808/17360=24.728\%$


设计	型号	日期	名称	图号
制图			THREAD	175/60R14 DMT-RC
校核			材料	比例 数量 备注
审核			重量	
工艺				
批准			DMACK TYRES LTD	




18"-225/40-18

DMACK Tyres









15"-195/50-15


DMACK Tyres



18"-225/40-18

DMACK Tyres








SUP. EMPTY DEPTH>5.5 > 17.0 %
SUP. EMPTY DEPTH>1.8 > 21.5 %
The sum of the width of the grooves encountered by a radial line is >16mm
The total width of the circumferential lines is >12mm


Class 9
Rim 8


[illegible]





























18"-235/40-18






In the control area
5.5mm grooves-18.1%
Total grooves-22.2%

----- Control area 170X140
Tyre weight 9.7kg

PRODUCT NAME
YOKOHAMA ADVAN A051T
PATTERN NAME
A051A
SIZE 210/65DR18



17"-190/625-17




In the control area
5.5mm grooves-18.2%
Total grooves-22.0%
----- Control area 148X140

PRODUCT NAME
YOKOHAMA ADVAN A051T
PATTERN NAME
A051A
SIZE 190/625R17


17"-210/625-17




SEC. A1-A2



SEC. B-B



SEC. C-C



SEC. E-E

In the control area
5.5mm grooves-17.9%
Total grooves-21.6%




----- Control area 170X140

PRODUCT NAME
YOKOHAMA ADVAN A051T

PATTERN NAME
A051A

SIZE 210/625R17

16"-190/600-16



In the control area
5.5mm grooves-18.1%
Total grooves-21.9%



----- Control area 148X140

PRODUCT NAME
YOKOHAMA ADVAN A051T


PATTERN NAME
A051A

SIZE 190/600R16


15"-190/580-15




SEC. A1-A2



SEC. B-B



SEC. C-C



SEC. E-E

In the control area
5.5mm grooves-18.2%
Total grooves-21.6%

Control area 148X140



PRODUCT NAME
YOKOHAMA ADVAN A051T

PATTERN NAME
A051A

SIZE 190/580R15

18" - 210/650R18

Product : Ventus Z205



Claass 9" (Rim 8")

Empty Depth > 5.5mm : 17.07%



Empty Depth > 1.8mm : 23.30%

GROOVE SURFACE AREA = 554540 mm²

Control Surface = 23800 mm²

17" - 210/625R17

Product : Ventus Z205



Class 9" (Rim 7.5")


Empty Depth > 5.5mm : 17.05%






Empty Depth > 1.8mm : 25.08%

Control Surface = 23800 mm²

17" - 180/625R17

Product : Ventus Z205



Sec. a-a	Sec. b-b	Sec. c-c
		
Sec. d-d	Sec. e-e1	
		

Class 8" (Rim 7")

Empty Depth > 5.5mm : 17.06%

Empty Depth > 1.8mm : 22.48%


8






GROOVE SURFACE AREA = 353483.2 mm²

Control Surface = 20720 mm²

16" - 180/600R16

Product : Ventus Z205



Sec. a-a	Sec. b-b	Sec. c-c
		
Sec. d-d	Sec. e-e1	
		

Class 8" (Rim 6.5")

Empty Depth > 5.5mm : 17.30%



Empty Depth > 1.8mm : 22.95%

GROOVE SURFACE AREA = 358456 mm²

Control Surface = 20720 mm²

15" - 200/580R15

Product : Ventus Z205



Class 9" (Rim 7.0")


Empty Depth > 5.5mm : 17.06%

Empty Depth > 1.8mm : 25.07%

Control Surface = 23800 mm²

18" - 210/650R18

Product : Ventus Z210





Class 9" (Rim 8")

a - a groove width / depth : 8.2 mm / 6.5 mm

b - b groove width / depth : 8.0 mm / 6.5 mm


Empty Depth > 5.5mm : 27.5%

Control Surface = 23800 mm²



17" - 180/625R17

Product : Ventus Z210




Width of Rim/Tyre Assembly : 7.5" ~ 8"

a - a groove width / depth : 7.2 mm / 6.5 mm

b - b groove width / depth : 7.0 mm / 6.5 mm


Empty Depth > 5.5mm : 27.5%

Control Surface = 20720 mm²



16" - 180/60R16

Product : Ventus Z210



Width of Rim/Tyre Assembly : 7.5" ~ 8"

a - a groove width / depth : 7.5 mm / 6.5 mm

b - b groove width / depth : 7.5 mm / 6.5 mm

Empty Depth > 5.5mm : 27.5%


Control Surface = 20720 mm²

SEC : a - a, b - b		
		
	a - a	7.5
	b - b	7.5



18" - 210/650R18

Product Name : Ventus Z215




Width of Rim/Tyre Assembly : 8.5" ~ 9"

Control Surface = 23800 mm²

> 5.5 mm : 17.10 %


> 1.8 mm : 21.53 %





17" - 190/630R17

Product Name : Ventus Z215




Width of Rim/Tyre Assembly : 7.5" ~ 8"

Control Surface = 20720 mm²

> 5.5 mm : 17.03 %


> 1.8 mm : 21.53 %





16" - 190/600R16

Product Name : Ventus Z215




Width of Rim/Tyre Assembly : 7.5" ~ 8"

Control Surface = 20720 mm²

> 5.5 mm : 17.10 %

> 1.8 mm : 21.54 %



18"-210/645R18



KUMHO TYRES


Moulded tyre for FIA homologation

Size : 210/645R18


Pattern : TM01

On the basis of a tread pattern width of 170mm and circumference of 140mm

- * The surface taken up by grooves at least 5.5 mm deep, with a maximum angle of 60° between the block in section and 2mm wide, must occupy at least 17% of the total surface.
- * The surface taken up by grooves at least 1.8 mm deep, with a maximum angle of 60° between the block in section and 2mm wide, must occupy at least 21.5% of the total surface.
- * The sum of the width of the grooves encountered by a radial line must be at least 16mm
- * At least 2 circumferential lines / Minimum total width of circumferential lines at least 12mm



Groove Area by 170 x 140 at least 1.8mm deep : 5815.4mm²
Void % : 24.4%
Groove Area by 170 x 140 at least 5.5mm deep : 4580.7mm²
Void % : 19.2%



18"-210/645R18


KUMHO TYRES

Moulded tyre for FIA homologation

Size : 210/645R18


Pattern : TM02

- On the basis of a tread pattern width of 170mm and circumference of 140mm
- * The surface taken up by grooves at least 5.5 mm deep, with a maximum angle of 60° between the block in section and 2mm wide, must occupy at least 17% of the total surface.
 - * The surface taken up by grooves at least 1.8 mm deep, with a maximum angle of 60° between the block in section and 2mm wide, must occupy at least 21.5% of the total surface.
 - * The sum of the width of the grooves encountered by a radial line must be at least 16mm
 - * At least 2 circumferential lines / Minimum total width of circumferential lines at least 12mm



Scale: 1:1

Groove Area by 170 x 140 at least 1.8mm deep : 5159mm²
Void % : 21.7%
Groove Area by 170 x 140 at least 5.5mm deep : 4446mm²
Void % : 18.7%



18"-210/645R18



KUMHO TYRES


Moulded tyre for FIA homologation

Size : 210/645R18

Pattern : TM02


On the basis of a tread pattern width of 170mm and circumference of 140mm:

- The surface taken up by grooves at least 5.5 mm deep, with a maximum angle of 60° between the block in section and 2mm wide, must occupy at least 17% of the total surface.
- The surface taken up by grooves at least 1.8 mm deep, with a maximum angle of 60° between the block in section and 2mm wide, must occupy at least 21.5% of the total surface;
- The sum of the width of the grooves encountered by a radial line must be at least 16mm
- At least 2 circumferential lines / Minimum total width of circumferential lines at least 12mm



Scale 1:1

Groove Area by 170 x 140 at least 1.8mm deep : 5159mm²
Void % : 21.7%
Groove Area by 170 x 140 at least 5.5mm deep : 4446mm²
Void % : 18.7%



17"-190/630R17



KUMHO TYRES


Moulded tyre for FIA homologation

Size : 190/630 R17


Pattern : TM02

On the basis of a tread pattern width of 148mm and circumference of 140mm:


- The surface taken up by grooves at least 5.5 mm deep, with a maximum angle of 60° between the block in section and 2mm wide, must occupy at least 17% of the total surface.
- The surface taken up by grooves at least 1.8 mm deep, with a maximum angle of 60° between the block in section and 2mm wide, must occupy at least 21.5% of the total surface.
- The sum of the width of the grooves encountered by a radial line must be at least 16mm
- At least 2 circumferential lines / Minimum total width of circumferential lines at least 12mm




Groove Area by 148 x 140 at least 1.8mm deep : 4579.1mm²
Void % : 22.1%
Groove Area by 148 x 140 at least 5.5mm deep : 3688.1mm²
Void % : 17.8%



Sec. A-A'




Sec. B-B'




Sec. C-C'



Sec. CA-CA'



Sec. H-H'



Sec. G-G'

16"-190/600R16




KUMHO TYRES

Moulded tyre for FIA homologation


Size : 190/600 R16

Pattern : TM02

- On the basis of a tread pattern width of 148mm and circumference of 140mm
- The surface taken up by grooves at least 5.5 mm deep, with a maximum angle of 60° between the block in section and 2mm wide, must occupy at least 17% of the total surface.
 - The surface taken up by grooves at least 1.8 mm deep, with a maximum angle of 60° between the block in section and 2mm wide, must occupy at least 21.5% of the total surface.
 - The sum of the width of the grooves encountered by a radial line must be at least 16mm
 - At least 2 circumferential lines / Minimum total width of circumferential lines at least 12mm



Groove Area by 148 x 140 at least 1.8mm deep : 4579.1mm²
 Void % : 22.1%
 Groove Area by 148 x 140 at least 5.5mm deep : 3584.5mm²
 Void % : 17.3%



15"-180/580R15



KUMHO TYRES


Moulded tyre for FIA homologation

Size : 180/580 R15

Pattern : TM02






On the basis of a tread pattern width of 148mm and circumference of 140mm

- The surface taken up by grooves at least 5.5 mm deep, with a maximum angle of 60° between the block in section and 2mm wide, must occupy at least 17% of the total surface
- The surface taken up by grooves at least 1.8 mm deep, with a maximum angle of 60° between the block in section and 2mm wide, must occupy at least 23.5% of the total surface
- The sum of the width of the grooves encountered by a radial line must be at least 16mm
- At least 2 circumferential lines / Minimum total width of circumferential lines at least 12mm



Scale 1:1

Groove Area by 148 x 140 at least 1.8mm deep : 4599.8mm²
 Void % : 22.2%
 Groove Area by 148 x 140 at least 5.5mm deep : 3563.8mm²
 Void % : 17.2%



18"-210/645R18


KUMHO TYRES

Moulded tyre for FIA homologation



Size : 210/645R18


Pattern : TW03

- On the basis of a tread pattern width of 170mm and circumference of 140mm
- The surface taken up by grooves at least 5.5mm deep must occupy at least 27.5% of the total surface.
 - The sum of the width of the grooves encountered by a radial line must be at least 16mm
 - At least 3 circumferential lines / Minimum total width of circumferential lines at least 4mm




Groove Area by 170 x 140 at least 5.5mm deep : 6789.4mm²
Void % : 28.5%





18"-225/40R18


Hoosier
RACING TIRE






18"-200/650R18


Hoosier
RACING TIRE

<UNITS = METRIC>




CONTROL SURFACE = 23,800mm²
GROOVES_> 5.5mm = 4,797.71mm² = 20.16%
GROOVES_> 1.8mm = 5,152.09mm² = 21.65%

[illegible]




Hoosier

RACING TIRE




CONTROL SURFACE = $20,720\text{mm}^2$
GROOVES $>5.5\text{mm}$ DEEP = 3617.7mm^2 = 17.46%
GROOVES $>1.8\text{mm}$ DEEP = 4638.2mm^2 = 22.39%




(8) TW'S PER CIRCUMFL GROOVE
AND TREAD ELEMENTS AS SHOWN.
(24) TOTAL FOR THE MOLD.


SEC A-A
(2X SCALE)




SEC B-B
(2X SCALE)



SEC C-C
(2X SCALE)



SEC D-D
(2X SCALE)



THIS IS A CAD DRAWING. MANUAL CHANGES ARE NOT PERMITTED.

Hoosier RACING TIRE CORP.
LAKEVILLE, INDIANA

195/50R17 TAHOE RALLY

S/N 4927


DRAWN BY: KTB APPROVED BY: KTB CHECKED BY: KTB
DATE: 04-09-2018 DATE: XX-XX-XXXX DATE: 04-09-2018
SCALE: 1:1 SCALE: 1:1 SCALE: 1:1
FILE: 195-50R17-195-50R17-195-50R17

2ND ANGLE PROJECTION

SHEET 1


16"-195/50R16

Hoosier
RACING TIRE




Hoosier

RACING TIRE




CONTROL SURFACE = $20,720\text{mm}^2$
GROOVES $>5.5\text{mm}$ DEEP = 3617.7mm^2 = 17.46%
GROOVES $>1.8\text{mm}$ DEEP = 4638.2mm^2 = 22.39%




(8) TWI'S PER CIRCUMFL GROOVE
AND TREAD ELEMENTS AS SHOWN.
(24) TOTAL FOR THE MOLD.


(3) TWI'S LOCATED
AS SHOWN IN PITCH
'S 4-10-12-18



SEC B-B
(2X SCALE)



SEC C-C
(2X SCALE)



SEC D-D
(2X SCALE)



THIS IS A CAR DRIVING. NO OTHER CHANGES ARE NOT PERMITTED.

Hoosier
RACING TIRE CORP.
LAKEVILLE, INDIANA


195/50R16 TARGO RALLY

S/N 4926

DRAWN BY: KES APPROVED BY: KES
DATE: 04-09-2018 DATE: XX-XX-XXXX CHECKED BY: KES
SCALE: 1:1 SHEET: 1



Hoosier

RACING TIRE



18"-205/640R18

TOYO TIRES



SEC.A1-A1




SEC.A2-A3



SEC.B1-B1



SEC.B2-B2



SEC.B3-B3




SEC.B4-B4



SEC.C1-C1



SEC.C2-C2



SEC.D1-D2



SEC.D3-D3

In the control area
5.5mm grooves-18.2%
total grooves 22.3%











Control area(170×140)

PRODUCT NAME
TOYO PROXES 888RT

SIZE 205/640R18

16"-185/600R16

TOYO TIRES





In the control area
5.5mm grooves-19.2%
Total grooves 23.1%

Control area(148x140)

PRODUCT NAME
TOYO PROXES 888RT
SIZE 185/600R16

15"-185/580R15

TOYO TIRES




SEC. A1-A1




SEC. A2-A3



SEC. B1-B1



SEC. B2-B2



SEC. B3-B3



SEC. B4-B4



SEC. C1-C1



SEC. C2-C2



SEC. D1-D2



SEC. D3-D3

In the control area
5.5mm grooves-18.22%
Total grooves 22.3%


Control area (161 x 140)

PRODUCT NAME
TOYO PROXES 888RT

SIZE 185/580R15




MRF TYRES





MRF TYRES





MRF TYRES

SECTION: 4-4

195 / 50 R15 ZWR1 TL

In the control area 148 x 140 mm (Indicated in the Dotted Line)

Grooved area within Min. 5.5 deep grooves > 27.5%

The total width of the circumferential line is >12 mm

The sum of the width of the grooves encountered by radial line is >16 mm

CLASS 8"

RIM 6.5"

F.I.A COMPLIANCE FOR 195/50 R15 ZWR1 TL

DRAWING		CHECKED/ISSUED		APPROVED		SCALE	
DATE	18.02.2021	DESIGNER	HEAD-DESIGN/DESIGN	ENGINEER / PWD	NTS		

COMPARTMENT TECHNICAL WOULD DESIGN


DATE NO. FA-0003

DATE DOCUMENT NO. 1

REVISION NO. 00




MRF TYRES





MRF TYRES



141

The sum of the width of the grooves encountered by a radial line is > 16 mm

140

DATE	DESCRIPTIONS	DRAWN	EXP'D / PDM

CHENNAI

242

INDIA

DRAWING

G. Kirubhakar

25.01.18

29.01.18

F.I.A COMPLIANCE FOR 195/5DR16 ZTA1 TL

CORPORATE TECHNICAL MOLD DESIGN	DRG. No. RR-195/5DR16_0518
---------------------------------	-----------------------------------

REVISION No. 00

SAP DOCUMENT TYPE		
SAP		

SAP DOCUMENT NO.

VER	
-----	--

00

IF IN DOUBT ASK.

[illegible]

NEW 2021



MRF TYRES

235 / 40 R18 ZTA PLUS TL

170.0

INSIDE

OUTSIDE



140.0

CLASS 9" 8.0" RIM

In the control area 170 x 140 mm (Indicated in the Dotted Line)

Grooved area within Min. 1.8 deep grooves > 21.5%
 Grooved area within Min. 5.5 deep grooves > 17.0%
 The total width of the circumferential line is >12 mm
 The sum of the width of the grooves encountered
 by radial line is >16 mm









15"-195/50R15



5.5m Groove - 17.74%
Total Grooves - 22.46%









Rim - 7.0"
Class - 8.0"

68"-195/50R68














5.5m Groove - 17.62%
Total Grooves - 22.35%

Rim - 7.0"
Class - 8.0"




5.5m Groove - 17.78%
Total Grooves - 22.50%
Rim - 7.0"
Class - 8.0"




5.5m Groove - 18.35%
Total Grooves - 23.23%


Rim - 8.0"
Class - 9.0"

Section M:M







18"-225/40R18




17"-224/45R17




15"-195/50R15




18"-210/650R18




17"-190/625R17



16"-200/600R16



18"-20/65R18




Name: EXTREME VRC

Size: 20/65-18

Width of the tyre/rim assembly: 224mm (8,8")


Control area: 170x140mm = 23800mm²
 Over 5,5mm depth grooves area = 4550mm² (19,12%)
 Over 1,8mm depth grooves area = 5118mm² (21,50%)

1,8mm ≤ groove depth ≤ 5,5mm
 5,5mm ≤ groove depth



Scale: 1:1

13"-20/54R13






Name: EXTREME VRC

Size: 20/54-13

Width of the tyre/rim assembly: 216mm (8,5")


Control area: 170x140mm = 23800mm²
Over 5,5mm depth grooves area = 4171mm² (17,55%)
Over 1,8mm depth grooves area = 5128mm² (21,55%)

1,8mm ≤ groove depth ≤ 5,5mm
5,5mm ≤ groove depth



Scale: 1:1

18"-28/66R18 -R-GT



Name: EXTREME VRC

Size: 28/66-18

Width of the tyre/rim assembly: 289mm


Class: RGT

Control area: 216x140mm = 30240mm²

Over 5,5mm depth grooves area = 6295mm² (20,82%)

Over 1,8mm depth grooves area = 7518mm² (24,86%)

1,8mm ≤ groove depth ≤ 5,5mm
5,5mm ≤ groove depth



Scale: 1:1

16"-19/60R16








Name: EXTREME VRC

Size: 19/60-16

Width of the tyre/rim assembly: 206mm (8,1

Control area: 161x140mm = 22540mm²
 Over 5,5mm depth grooves area = 4518mm² (20,04%)
 Over 1,8mm depth grooves area = 4855mm² (21,54%)

1,8mm ≤ groove depth ≤ 5,5mm
 5,5mm ≤ groove depth



Scale: 1:1

15"-19/58R15








Name: EXTREME VRC

Size: 19/58-15

Width of the tyre/rim assembly: 207mm (8,1"

Control area: 161x140mm = 22540mm²
Over 5,5mm depth grooves area = 4530mm² (20,10%)
Over 1,8mm depth grooves area = 4852mm² (21,53%)

1,8mm ≤ groove depth ≤ 5,5mm
5,5mm ≤ groove depth



Scale: 1:1